


Nextiva

S4300-RP Outdoor Wireless Repeater

At A Glance



Wireless repeater for retransmitting signals from Nextiva wireless devices to a wired LAN

Resolves “hidden node” and quality of service problems typical of conventional Wi-Fi 802.11 products

Built-in wireless site survey tools for simplified installation

Ideal for outdoor, wireless point-to-point and point-to-multipoint applications, such as critical infrastructure and city surveillance deployments

Why Verint? The industry’s only wireless solutions with integrated radios, encoders, and antennae in compact, NEMA-rated enclosures for reduced deployment costs and reliable operation

The Nextiva® S4300-RP, consisting of two units, is an outdoor wireless repeater that may be used as a range extender for wireless links — that is, when a device is needed to retransmit signals from Nextiva wireless products to a wired LAN. This is especially useful in long-distance deployments or when transmitting around RF path obstructions.

The S4300-RP can function as a repeater in both point-to-point and point-to-multipoint outdoor applications.

Easy, Cost-Effective Deployment

The S4300-RP is equipped with built-in wireless site survey tools to facilitate installation and ensure optimal configuration. In addition, the wireless repeater supports remote configuration and firmware upgrade from any node on the network.

High Performance and Reliability

The S4300-RP enables organizations to transmit images from virtually *anywhere* with high reliability.

The S4300-RP uses the 2.4 GHz or 5 GHz license-free wireless band or the 4.9 GHz US public safety band, and comes with a built-in multi-band antenna that allows users to switch wireless frequencies just by reconfiguring the software, instead of replacing the entire unit.

The industry-leading Verint® SPCF/SDCF polling protocol resolves Wi-Fi “hidden node” and quality of service problems characteristic of conventional 802.11 products, with no degradation in video signal quality over extended range transmissions.

SSL-based authentication helps secure configuration access, and AES encryption with rotating 128-bit key enables a high level of security during wireless video transmission.

Nextiva Control Center, an easy-to-use management portal, simplifies installation and allows users to centrally administer and configure the S4300-RP. Nextiva HealthCheck™ continuously monitors the performance of the S4300-RP, with automated diagnostics and problem-solving assistance for greater uptime and lower service costs.

The S4300-RP is part of the Nextiva portfolio of wireless edge devices, which lead the industry in innovation and value. Built on accepted industry standards, these intelligent edge devices are designed for high availability, easy interoperability with IT infrastructure and video equipment, and superior performance.

Technical Specifications

NETWORK	
RF Interface	Nextiva SDCF for backbone applications Nextiva SPDF for point-to-multipoint applications 802.11a/802.11g PHY with proprietary MAC protocol
Frequency	2.40-2.4835 GHz (ISM) 4.940-4.990 GHz (Public safety band) 5.250-5.350 GHz (U-NII-2) Not available in US & Canada 5.470-5.725 GHz (DFS) Not available in US & Canada 5.725-5.825 GHz (U-NII-3/ISM)
Modulation	OFDM
Maximum Output Power	2.4 GHz: 13 dBm 4.9 GHz: 20 dBm 5.x GHz: 23 dBm
Range (RF Line of Sight)	2.40-2.4835 GHz (8.5 dBi): up to 2.1 miles (3.4 km) 4.940-4.990 GHz (12 dBi): up to 2.4 miles (3.9 km) 4.940-4.990 GHz (18 dBi): up to 8.2 miles (13.2 km) 5.725-5.825 GHz (12 dBi): up to 2.1 miles (3.4 km) 5.725-5.825 GHz (19 dBi): up to 6.2 miles (10.0 km)
Data Rate (Max Burst Rate) Channels	6, 9, 12, 18, 24, 36, 48, and 54 Mbps 2.4 GHz: 11, 3 non-interfering 4.9 GHz: 2, 4, or 10 depending on user-configurable channel width, non-interfering 5.3 GHz: 4, non-interfering 5.4 GHz: 11, non-interfering (DFS) 5.8 GHz: 5, non-interfering
Encryption Protocols	128-bit AES with auto-key rotation RTP/IP, UDP/IP, TCP/IP, or multicast IP DNS and DHCP client
Security	SSL-based authentication
LED Indicator	Status, wireless activity, LAN activity
Antenna Connector	SMA female
Ethernet Connector	Weatherproof 10/100Base-T (RJ-45)
POWER	
Input Voltage	24V AC +/- 20% and 12V DC +/- 10%
Maximum Consumption	20W (1.6 A at 12V DC), 25 VA at 24V AC
Power Connector	Weatherproof circular
PHYSICAL	
Enclosure	NEMA 4X/IP 66 powder coat painted die-cast aluminum with wall-mount brackets
Size	8.75L x 3.5W x 5.5H in. (222L x 89W x 140H mm)
Weight	4.6 lbs (2.1 kg) including mounting brackets
Environmental	-22°F to 122°F (-30°C to 50°C)
Humidity	100% at 122°F (50°C)
MANAGEMENT	
Configuration	Remote: via Nextiva, SConfigurator, Internet Explorer 5.0 or 6.0, or Telnet Local: via the Ethernet port using SConfigurator or via Internet Explorer 5.0 or 6.0
Firmware Upgrade	Via the Ethernet port of the network
CERTIFICATIONS	
USA	RoHS compliant, UL certified FCC CFR47 Part 15 Subpart B, C, and E (15.247, 15.407, 15.107, 15.109) FCC Part 90 DSRC-C mask certification
Canada	UL60950-1, First Edition Industry Canada RSS-210, RSS-139, and ICES-003 CSA C22.2 NO. 60950-1, First Edition
MODELS	
S4300-RP	Outdoor 2.4/5.x GHz wireless Ethernet repeater (12V DC/24V AC input) with 6-foot (2-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets, and multi-band antennae
S4300-RP-49 Public Safety	Outdoor 2.4/4.9/5.x GHz wireless Ethernet repeater (12V DC/24V AC input) with 6-foot (2-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets, and multi-band antennae
WARRANTY	
	2-year limited warranty covering parts and labor*

* Warranty information applies to the Americas only. Consult your Verint representative for warranty details for other regions.

Verint. Powering Actionable Intelligence.®

Verint® Systems Inc. is a leading provider of actionable intelligence™ solutions for an optimized enterprise and a safer world. More than 10,000 organizations in over 150 countries rely on Verint solutions to perform more effectively, build competitive advantage, and enhance the security of people, facilities, and infrastructure.

videoinfo@verint.com
1-866-NEXTIVA
www.verint.com/videosolutions
330 South Service Road
Melville, NY 11747 USA

April 2008
Version 2.0
VINED070408U

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Features listed in this document are subject to change. Please contact Verint for current product features and specifications.

All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2008 Verint Systems Inc. All Rights Reserved Worldwide.